



Three Phase Hybrid Inverter


8-12KW LV Series

- 100% three-phase unbalanced output, with each phase capable of delivering up to 50% of the rated power
- AC couple to retrofit existing solar system
- Max. 10 pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel
- Max. charging/discharging current of 240A
- 48V low voltage battery, transformer isolation design
- Time periods for battery charging/discharging
- Support storing energy from diesel generator

Product Characteristics



Application System Diagram



Technical Properties

Model	8		10	12
PV String Input				
Max. DC Input Power (W)	10400		13000	15600
Rated PV Input Voltage (V)	550 (160-800)			
Start-up Voltage (V)	160			
MPPT Voltage Range (V)	200-650			
Full Load MPPT Voltage Range (V)	350-650			
Max. DC Input Current(A)	13+13	26+13		
Max. DC Short Circuit Current(A)	17+17	34+17		
No.of MPPT Trackers	2			
No.of Strings per MPPT Tracker	1+1	2+1		
AC Output				
Rated AC Output Power (W)	8000	10000	12000	
Max AC Output Power (W)	8800	11000	13200	
AC Output Rated Current (A)	12.1	16.7	18.2	
Max AC Output Current (A)	13.4	18.4	20	
Max Output short circuit current (A)	75			
Max. Continuous AC Passthrough(A)	45			
Peak Power (off grid)	2 times of rated power, 10 S			
Power Factor	0.8 leading to 0.8 lagging			
Output Frequency and Voltage	50/60Hz; 3L/N/PE 220/380Vac, 230/400Vac			
Grid Type	Three Phase			
Total Harmonic Distortion (THDi)	<3% (of nominal power)			
DC Current Injection	<0.5% In			
Battery				
Battery Type	Lead-acid or Lithium-ion			
Battery Voltage Range (V)	40-60			
Max. Charging Current (A)	160	200	240	
Max. Discharging Current (A)	160	200	240	
External Temperature Sensor	Yes			
Charging Curve	3 Stages / Equalization			
Charging Strategy for Li-Ion Battery	Self-adaption to BMS			
Efficiency				
Max PV Conversion Efficiency	97.6%			
European Efficiency	97.0%			
MPPT Efficiency	99.0%			
Protection				
Anti-islanding Protection	Yes			
PV String Input Reverse Polarity	Yes			
Insulation Resistor Detection	Yes			
Residual Current Monitoring Unit	Yes			
Output Over Current Protection	Yes			
Output Shorted Protection	Yes			
Output overvoltage protection	Yes			
Photovoltaic input lightning	Yes			
Surge Protection	DC Type III / AC Type III			
Over Voltage Category	DC Type II/AC Type III			
Certifications and Standards				
Grid Regulation	IEC61727/62116,EN50549-1			
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2			
General				
Operating Temperature Range (°C)	-40-60°C, >45°C Derating			
Cooling	Smart Cooling			
Noise (dB)	≤50 dB			
Communication with BMS	RS485; CAN			
Monitoring mode	WIFI, APP			
Weight (kg)	37.5			
Size (W x H x D mm)	702×422×281 (Excluding Connectors and Brackets)			
Protection Degree	IP65			
Installation Style	Wall-mounted			
Warranty	5 Years (10 Years Optional)			